



Deltech Outdoor IR Bullet Audio Line-in Camera

Model : DS-212CSA1P

Main Features:

- * H.265/H.264 Encoding
- * 100dB Double shutter WDR, 3D/2D DNR
- * Plug and Play with RDS NVR
- * Dual stream, motion detection, PSW protection
- * Free P2P, CMS, Professional "viewcan" Mobile App.
- * Audio Line-in Supported
- * Onvif 2.6.1 Supported
- * USB Recording Optional (+\$1.5)



| Camera | |
|---------------------------|--|
| Sensor | 1/2.9" 2M SONY Exmor CMOS Sensor |
| Min Illumination | 0.01Lux@F1.2 (0Lux,IR on) |
| S/N | ≥50dB(AGC OFF) |
| WDR | 100dB Double shutter WDR |
| IR LEDs | 2 pcs IR Array |
| IR Range | 30m |
| Lens | 3.6mm |
| Current | 350mA |
| Power Consumption | <4.5W |
| Weight | 350g |
| IP Rating | IP66 |
| Interface | |
| Ethernet | RJ45 10M/100M |
| Audio Input | Audio Line-in Supported |
| Video Encode | |
| Encoding | H.265/H.264 |
| Resolution(Main Stream) | 1920*1080/1280*960/1280*720/704*480, 1-25(30)fps |
| Resolution(Substream1) | 704*480/640*480/352*240 |
| Resolution(Substream2) | 1280*720/960*540/640*480 |
| Video Compression | 64Kbps-8Mbps Continuously adjustable, Support CBR/VBR |
| Subtitle Overlay | Support Channel Name, Date&Time,Stream Information Overlay,Overlay Position adjustable |
| Data Transfer and Storage | |
| Data Storage | Video, Image |
| Storage Mechanism | Manual, Auto(Loop, Timing,Alarm Switch Input, Motion Detection) |
| Alarm Data Transfer | FTP, E-mail, Brower, Management Software |
| Network Protocol | HTTP,TCP,ARP,RTSP,RTP,UDP,RTCP,SMTP,FTP,DHCP,DNS,DDNS,PPPoE,IPv4, U PnP,NTP |
| Client-Side Browse | IE,firefox |
| ONVIF Protocol | ONVIF 2.6.1 |
| General Parameters | |
| Input Voltage | DC12V±10%/POE |
| Working Temperature | -10°C~+50°C |
| Working Humidity | <90%RH(No Condensation) |