

MODEL: DS-HVR1104

Features:

- Support AHD-H series front-end non-real-time encoding;
- Support VGA, HDMI HD output;
- Support XM Cloud technology, easy to achieve a variety of network penetration, one step to remote monitoring, getting rid of various complicated network settings, easy and simple to operate;
- Support various mobile monitoring: (IOS, Android) .
- Support multiple web browsers (IE,Chrome,Firefox,Safari) ;
- Support more than 20 languages, no nation boundaries;
- perfect protection circuit, unique triple watchdog function
- Supporting web, CMS, center platform management software MYEYE, provide SDK development.

Parameter:

	Model	ADVR7004T-MH
System	Main processor	Huawei Hi 3521
Video	video codec	H.264(High Profile);
	Encode	4*AHD-H@15fps
	Decode	4*AHD-H@15fps
Audio	Multi-mode input	Pure Analog: 4*AHD-H, 4*AHD-M ; Mixed: 4*AHD-M(analog)+4*720P(network); Pure Network: 2*1080P+2*720P;8*720P ;
	Audio compression	G.711A
Recording and Playback	Intercom	support
	Record mode	Manual>alarm>motion detection>timing
Storage and backup	Playback Channels	4
	Space occupation	1080P: 20G~30G/ day*channel 960H: 12~20G/ day*channel 720P: ~20G/ day*channel audio: 691.2M/ day*channel
	Backup mode	Network backup, USB HDD, USB writer, SATA writer
Interface	Video input	4 BNC
	Video output	1ch VGA,1ch HDMI
	Audio input	4ch RCA
	Audio output	1ch RCA
	Alarm input	No
	Alarm output	No
	Network Interface	RJ45 10M/100M Adaptive Ethernet port
	PTZ control	RS485; support multiple PTZ protocols
	USB	2 USB ports
	Hard disk	1 SATA (Each maximum support 4T)
	Wireless	3G, WIFI(expand via USB)
Other	Power	12V/2A
	dimension	255mm(length)* 236mm(width)* 44mm(height)

