

# MODEL: DS-HVR1208

## Features:

- Support AHD-H series front-end non-real-time encoding;
- Support VGA, HDMI HD output;
- Support XM Cloud technology, easy to achieve a variety of network penetration, one step to remote monitoring, getting rid of various complicated network settings, easy and simple to operate;
- Support various mobile monitoring: (IOS, Android) .
- Support multiple web browsers (IE,Chrome,Firefox,Safari) ;
- Support more than 20 languages, no nation boundaries;
- perfect protection circuit, unique triple watchdog function
- Supporting web, CMS, center platform management software MYEYE, provide SDK development.

## Parameter:

	Model	ADVR7008T-MH	
System	Main processor	Huawei HI 3531	
Video	video codec	H.264(High Profile):	
	Encode	8*AHD-H@15fps	
	Decode	4*AHD-H@15fps	
Video	Multi-mode input	Pure Analog: 8*AHD-H, 4*AHD-H, 8*AHD-M; Mixed: 2*AHD-H(analog)+2*1080P(network); 8*AHD-M(analog)+8*720P(network); Pure Network: 4*1080P, 1*1080P+8*720P, 20*960H	
	Audio compression	G.711A	
Audio	Intercom	support	
	Record mode	Manual>alarm>motion detection>timing	
Recording and Playback	Playback Channels	4	
	Space occupation	1080P: 20G~30G/ day*channel 960H: 12~20G/ day*channel 720P: ~20G/ day*channel audio: 691.2M/ day*channel	
Storage and backup	Backup mode	Network backup, USB HDD, USB writer, SATA writer	
	Video input	8 BNC	
Interface	Video output	1ch VGA,1ch HDMI	
	Audio input	4ch RCA	
	Audio output	1ch RCA	
	Alarm input	No	
	Alarm output	No	
	Network interface	RJ45 10M/100M Adaptive Ethernet port	
	PTZ control	RS485: support multiple PTZ protocols	
	USB	2 USB ports	
	Hard disk	1 SATA (Each maximum support 4T )	
	Wireless	3G、WIFI(expand via USB)	
	Other	Power	12V/2A
		dimension	255mm(length)*236mm(width)*44mm(height)

