

## DS-7200HQHI-F1/N SERIES TURBO HD DVR



### Features and Functions

- Connectable to AHD, HD-TVI, network and analog cameras;
- Support HIKVISION-C protocol for connecting camera over coax;
- Support enabling H.264+ to ensure high video quality with lowered bitrate;
- Provide HDMI, VGA and CVBS outputs, and simultaneous HDMI/VGA output at up to 1920×1080p resolution;
- One-key recording configurable;
- Redundant recording and holiday recording;
- Main stream and sub-stream parameters configurable for simultaneous recording;
- Support channel-zero encoding;
- Support 1080p lite mode enabled to realize the real-time 1080p lite and 720p lite resolution;
- Instant playback for assigned camera in live view mode;
- Up to 4/8-ch synchronous playback at 1080p resolution;
- Playback at up to 256X speed;
- Main stream and sub-stream selectable for local/remote playback;
- Playback by smart search (motion/intrusion/line crossing detection triggered recording);
- Playback by VCA search;
- Customization of tags, searching and playing back by tags;
- Manual VQD (video quality diagnostics);
- Supports locking and unlocking of video files;
- HDD quota and group management;
- Two SATA interfaces for DS-7208HQHI-F2/N and one SATA interface for DS-7200HQHI-F1/N;
- One self-adaptive 10M/100Mbps network interface;
- Supports access by EZVIZ Cloud P2P;
- Supports Hikvision DDNS (Dynamic Domain Name System).



## Specifications

Model	DS-7204HQHI-F1/N		DS-7208HQHI-F1/N	
Video/Audio input	Video compression	H.264		
	Analog video input	4-ch	8-ch	
		BNC interface (1.0Vp-p, 75 Ω), supporting coaxitron connection		
	Supported HD TVI input	1080p/25Hz, 1080p/30Hz, 720p/25Hz, 720p/30Hz, 720P/50Hz, 720p/60Hz		
	Supported AHD input	720p/25Hz, 720p/30Hz		
	IP video input	1-ch	2-ch	
		Up to 1080p resolution		
Audio compression	G.711u			
Audio input/Two-way audio input	1-ch, RCA (2.0 Vp-p, 1 KΩ)			
Video/Audio output	CVBS output	1-ch, BNC (1.0 Vp-p, 75 Ω), resolution: PAL: 704 × 576, NTSC: 704 × 480		
	HDMI/VGA output	1920 × 1080/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz		
	Encoding resolution	When 1080p Lite mode not enabled: 1080p(non-real-time)/720p/VGA/WD1/4CIF/CIF; When 1080p Lite mode enabled: 1080p lite/720p lite/720p/VGA/WD1/4CIF/CIF		
	Frame rate	Main stream: 1/16 fps to Real time frame rate		
		Sub-stream: WD1/4CIF@12fps, CIF/QVGA/QCIF@ real time frame rate		
	Video bitrate	32 Kbps to 6 Mbps		
	Audio output	1-ch, RCA (Linear, 1KΩ)		
	Audio bitrate	64 Kbps		
	Dual-stream	Support		
	Stream type	Video, Video & Audio		
Synchronous playback	4-ch	8-ch		
Network management	Remote connections	128		
	Network protocols	TCP/IP, PPPoE, DHCP, EZVIZ Cloud P2P, DNS, DDNS, NTP, SADP, NFS, iSCSI, UPnP™, HTTPS, ONVIF		
Hard disk	SATA	1 SATA interface		
	Capacity	Up to 6TB capacity for each disk		
External interface	Network interface	1; 10M/100Mbps self-adaptive Ethernet interface		
	Serial interface	1; standard RS-485 serial interface, half-duplex		
	USB port	2 × USB 2.0		
General	Power supply	12 VDC		
	Consumption (without hard disks)	≤ 15 W	≤ 20 W	
	Working temperature	-10 °C to +55 °C (14 °F to 131 °F)		
	Working humidity	10% to 90%		
	Chassis	Standalone 1U chassis		
	Dimensions(W × D × H)	315 × 242 × 45 mm (12.4 × 9.5 × 1.8 inch)		
Weight(without hard disks)	≤ 2 kg (4.4lb)			

## Specifications

Model		<b>DS-7208HQHI-F2/N</b>
<b>Video/Audio input</b>	<b>Video compression</b>	H.264
	<b>Analog video input</b>	8-ch BNC interface (1.0Vp-p, 75 Ω), supporting coaxitron connection
	<b>Supported HD TVI input</b>	1080p/25Hz, 1080p/30Hz, 720p/25Hz, 720p/30Hz, 720P/50Hz, 720p/60Hz
	<b>Supported AHD input</b>	720p/25Hz, 720p/30Hz
	<b>IP video input</b>	2-ch Up to 1080p resolution
	<b>Audio compression</b>	G.711u
	<b>Audio input/Two-way audio input</b>	1-ch, RCA (2.0 Vp-p, 1 KΩ)
<b>Video/Audio output</b>	<b>CVBS output</b>	1-ch, BNC (1.0 Vp-p, 75 Ω), resolution: PAL: 704 × 576, NTSC: 704 × 480
	<b>HDMI/VGA output</b>	1920 × 1080/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz
	<b>Encoding resolution</b>	When 1080p Lite mode not enabled: 1080p(non-real-time)/720p/VGA/WD1/4CIF/CIF; When 1080p Lite mode enabled: 1080p lite/720p lite/720p/VGA/WD1/4CIF/CIF
	<b>Frame rate</b>	Main stream: 1/16 fps to real time frame rate Sub-stream: WD1/4CIF@12fps, CIF/QVGA/QCIF@ real time frame rate
	<b>Video bitrate</b>	32 Kbps to 6 Mbps
	<b>Audio output</b>	1-ch, RCA (Linear, 1KΩ)
	<b>Audio bitrate</b>	64 Kbps
	<b>Dual-stream</b>	Support
	<b>Stream type</b>	Video, Video & Audio
	<b>Synchronous playback</b>	8-ch
<b>Network management</b>	<b>Remote connections</b>	128
	<b>Network protocols</b>	TCP/IP, PPPoE, DHCP, EZVIZ Cloud P2P, DNS, DDNS, NTP, SADP, NFS, iSCSI, UPnP™, HTTPS
<b>Hard disk</b>	<b>SATA</b>	2 SATA interfaces
	<b>Capacity</b>	Up to 6TB capacity for each disk
<b>External interface</b>	<b>Network interface</b>	1; 10M/100Mbps self-adaptive Ethernet interface
	<b>Serial interface</b>	1; standard RS-485 serial interface, half-duplex
	<b>USB port</b>	2 × USB 2.0
<b>General</b>	<b>Power supply</b>	12 VDC
	<b>Consumption (without hard disks)</b>	≤ 20W
	<b>Working temperature</b>	-10 °C to +55 °C (14 °F to 131 °F)
	<b>Working humidity</b>	10% to 90%
	<b>Chassis</b>	380 mm 1U chassis
	<b>Dimensions(W × D × H)</b>	380 × 320 × 45 mm (15.0 × 12.6 × 1.8 inch)
	<b>Weight(without hard disks)</b>	≤ 2 kg (4.4lb)