



# COLOUR DOME CAMERA

**ADV 20F**



## SPECIFICATION

Model	ADV 20F
Image Sensor	1/4" Sharp CCD Color Sensor
Scanning System	2:1 Interlace
	30 Frames (NTSC)    25 Frames (PAL)
	525 Lines Interlaced (NTSC)    625 Lines Interlaced (PAL)
Effective Pixels	512 (H) x 492 (V) (NTSC)    512 (H) x 582 (V) (PAL)
Resolution	380 TV Lines
Minimum Illumination	1.0 Lux / F 2.0
S/N Ratio	More Than 48dB (AGC Off)
Video Output	1.0 Vp-p composite, 75ohm
Gamma Ratio	0.45
White Balance	Auto
Back Light Compensation	Auto
Auto Gain Control	Auto
Iris Mode	AES
Synchronization	Internal
Electronic Shutter	1/60 to 1/100,000 sec (NTSC)    1/50 to 1/100,000 sec (PAL)
Lens	f = 3.6mm / F2.0
Power Source	DC12V ± 10%
Power Consumption	120mA
Operating Temperature	- 5°C to + 45°C
Weight / Dimension	Approx. 180g / Ø 87.0 x 58.0H mm

*Design and specifications are subject to change without prior notice*

